


## BEXCOFLEX 8 STRAND



### Construction

Plaited ropes are well established in marine and off-shore applications, because of their ease in handling and non-rotating behaviour. They are produced on a plaiting machine containing eight reels, each containing one strand, groups of two reels interweave as a pair around the other pairs of reels to produce an eight strands rope of a somewhat square cross section. No twist is taken out of the strand during manufacturing, which is important for large size ropes.

### Material Properties


BexcoFlex is a mixed or composite fibre based on our proprietary BEX- yarn and polyester as a strength member. It combines the excellent fatigue characteristics and abrasion resistance of polyester with the low density of nylon. The fatigue life is comparable to pure polyester, but the weight for a given strength is comparable to that of nylon, giving the rope excellent handling characteristics. A special marine finish is applied to further increase the wear resistance in a marine environment. This finish has been tested conform ASTM D6611-00 and is water repellent. Wet and dry strength is identical.

### Features

➤	<b>Material</b>	High tenacity BEX-yarn High tenacity polyester
➤	<b>Construction</b>	8 strand plaited
➤	<b>Treatment</b>	Marine finish
➤	<b>Colour of Rope</b>	White plus a red marker yarn
➤	<b>Approx. Spec. Density</b>	1,1 non floating
➤	<b>Melting point</b>	165°C / 260°C
➤	<b>Abrasion Resistance</b>	Very good
➤	<b>U.V. resistance</b>	Good
➤	<b>Temperature resistance</b>	70°C max continuous
➤	<b>Chemical resistance</b>	Good, solvents and strong oxidisers may have a mild effect
➤	<b>Dry &amp; wet conditions</b>	Wet strength equals dry strength
➤	<b>Range of use</b>	Fishing, inland shipping, merchant, navy, industry, mooring
➤	<b>Coil length</b>	220m
➤	<b>Spliced strength</b>	± 10% lower
➤	<b>Weight and length tolerance</b>	± 5%
➤	<b>Diameter</b>	± 2%

# BEXCO

Dia	Circ.	Min Break Load		Weight	
		tf	kN	kg/100m	kg/coil
32	4	30,6	300	68,5	151
36	4 1/2	35,2	345	79,5	175
40	5	42,5	417	96,6	213
44	5 1/2	49,1	482	112	247
48	6	55,7	546	128	282
52	6 1/2	64,2	630	149	327
56	7	72,7	713	169	372
60	7 1/2	81,1	796	190	417
64	8	90,3	886	211	465
68	8 1/2	104	1025	246	542
72	9	113	1107	267	587
76	9 1/2	134	1315	315	692
80	10	148	1448	348	765
88	11	175	1719	415	913
96	12	205	2014	489	1076
104	13	235	2308	563	1238
112	14	269	2639	646	1421
120	15	301	2951	725	1594
128	16	339	3330	821	1806
136	17	379	3722	920	2024
144	18	416	4081	1011	2225
152	19	464	4551	1131	2489
160	20	507	4971	1239	2726



MBL = **M**inimum **B**reaking **L**oad conform ISO 2307

Other sizes available upon request

The information disclosed herein was originated by and is the property of **BEXCO** nv and its subsidiaries. **BEXCO** nv and its subsidiaries reserves all intellectual and industrial property rights such as any and all patent, trademark, design, manufacturing, reproduction use and sales rights thereto and to any article disclosed therein, except to the extent rights expressly granted to others.